ETOZ HYD OIL



Product Data Sheet

Description:

ETOZ HYD Anti-wear Hydraulic Oil is a premium quality anti-wear hydraulic fluid designed for service in mobile and stationary high pressure hydraulic systems.

It contains a stabilized zinc additive system which provides outstanding anti-wear characteristics and good thermal and oxidation stability.

Standards:

ETOZ HYD Anti-wear Hydraulic Oil is recommended for use in all hydrodynamic power transmission machinery, hydraulic controls and hydrostatic systems in various industries.

It can be used in lubrication of pumps and other industrial machinery. It is also suitable for use in mobile hydraulic systems.

Benefits:

- Versatile, premium oil for many applications.
- Oxidation inhibitor prevents oil from thickening
- Protects against wear & scuffing in hydraulic pumps.
- Protects against rust and corrosion.
- Foam inhibited to prevent pump cavitations.

Certificate of Analysis :-

ISO	32	46	68	100
Kinematics Viscosity				
cSt @ 40 ℃ D445	32	46	68	100
cSt @ 100 ℃ D445	5.2	6.4	8.8	10.5
Viscosity Index D2270	101	100	98	98
Zinc, mass %	0.06	0.06	0.06	0.06
Pour Point , ℃ D97	-9	-9	-9	-9

^{*} Values Shown Here Are Typical And May Vary.

Precautions

ETOZ Hydraulic Oil is manufactured from high quality petroleum base stocks, blended with quality additives. As with all petroleum products, good personal hygiene and careful handling should always be practiced. Avoid prolonged contact to skin, splashing into eyes, ingestion or vapour inhalation.